



ART. 515
Brass ball valve, standard port, F-F, with aluminium T-handle. Size from 1/2" to 1 1/4"

SPECIFICATION	
Series	500
Thread ends	Female-Female:ISO 228/1
Orifice	from 15 to 32 mm
Actuator	90° Rotation with mechanical stop
Operator	Aluminium T-Handle

APPLICATION

Assembly in rigid pipe system
 Nominal pressure (PN) in bar: 20-40
 KV: flowrate coefficient m³/h
 Direction of flow: as desired
 Temperature range: -20 °C / +120°C
 Use: Water



N°	Descrizione	Description	Materials	Treatment	Q.ty
1	Corpo	Body	CW617N	Nickel-Plated	1
2	Mancotto	End Connection	CW617N	Nickel-Plated	1
3	Guarnizione	Ball seal	PTFE		2
4	Sfera	Ball	CW617N	Ni+Cr	1
5	Perno	Stem	CW614N		1
6	Guarnizione inferiore	Lower seal	PTFE		1
7	O-Ring	O-Ring	NBR70sh		1
8	Guarnizione superiore	Upper seal	PTFE		1
9	Dado	Nut	STEEL UNI 5771	Zinc-Plated	2
10	Rondella	Brass ring	CW614N		1
11	Farfalla	T-handle	ALUMINIUM	Painted	1

Denominazione particolare / Name: Valvola a sfera, passaggio standard, F-F, con farfalla in alluminio

Forma / Format: A3
 Graio / Project code: MEDIA UNI-ISO 2768/1

Disegnato / Designed by: [Logo]
 Approvato / Approved by: [Logo]

Scala / Scale: 1:1
 Foglio / Tab: 1/1

Trattato / Treaty Code: [Logo]
 Rugosità Decimale: 32 / (32)
 General roughness: 32 / (32)

Valido per / Available for: Consultazione

Materiali / Material: [Logo]

Testi / Superficie / Surface / Testi / Termico / Thermal Treat. Serie / Project N°: [Logo]

N° Disegno / Drawing N°: Art.515

Sezione / Section: -

Peso / Weight: - g

Altura / Size: 1/2" - 1 1/4"

TDM BRASS

UFFICIO TECNICO

DN	G	A	B	C	D	Ch	KV	PN
15	1/2"	47	40.5	53	10	25	11.2	40
20	3/4"	55	43	53	11	31	23.5	25
25	1"	65	53.5	63	13	38	32	25
32	1 1/4"	74	58.5	73	14	47	67.2	20